Galar

Additional information please contact:

Borr Drilling Limited

E. Pearman Building, 2nd Floor 9 Par-la-Ville Road, Hamilton HM11, Bermuda

marketing@borrdrilling.com - www.borrdrilling.com

High Specification Jackup

General Description		
Design / Generation	PPL Pacific Class 400	
J	PPL Shipyard PTE Ltd., Singapore	
•	Significant Upgrades2017	
	ABS,A1, Self-Elevating Drilling Unit	
Flag	Liberia	
Overall Dimensions	236.5 ft.long x 224.4 ft.wide x 27.9 ft deep	
Legs	(3) 532 ft. long, Triangular	
Drafts	19.50 ft at loadline	
Accommodation	150 persons	
Displacement	43,845 kips	
Variable Deck		
Transit Speed	up to 4 knots, @ 150st bollard pull	
Operating Water Depth	400 ft. designed / 400 ft. outfitted	
Maximum Drilling Dept	h	
Drilling Equipment		
Derrick	Loadmaster Derrick 160 ft. high, with 35 ft. x 35 ft. base	
Hookload Capacity	1,500,000lbs gross nominal capacity	
Cantilever/ Drill floor	75 ft / 15 ft Port & Stbd	
Drawworks	Cameron Ultrahoist 750-3000(FA30) Max hook load 750st with 14 lines. 2 x GE AC motors suitable for 1-5/8" drill line	
Rotary Table	Cameron 49-1/2" table opening, hydraulic drive, rated 750st	
Top Drive	Cameron FD35, 750st static/dynamic load rating 1150hp AC motor GE. Max speed 274rpm, Max torque 66,000 ftlbs. Max MU/BO Torque 115,000ft-lbs, (2) IBOP 3 1/6" – 15k	
Tubular Handling	Cameron JiM 10 T-P-L, 3-1/2" to 9-3/4" OD drill pipe & drill collar Make-up torque 103,300ft-lb Break-out torque 147,500ft-lb Spinning speed 0-80 rpm (with 5" OD) Spinning torque 3,500ft-lbs	
Mud Pumps	(3) Lewco W2214 triplex pumps, each driven by 1150 hp (GEAC motor) 7,500 psi rated	
Solids Control	(4) NOV Brandt VSM 300 shaleshakers. Mud cleaner installed over one shale shaker.	
Power & Machinery		
Main Power	(5) Caterpillar 3516C-HD diesel engines rated 2,150hp at 1200rpm each with Kato generator rated to 2,150 KVA	

(1) Caterpillar 3508B DITA diesel engine rated 1,298hp at

1,800rpm with Leroy Somer generator rated to 1020kv

n Jackup		
Storage Capacities		
Fuel Oil		
Liquid Mud		
•		
	1,289 bbls	
	21,742 bbls	
	(mud + cement) 11,653 cu-ft	
Sack Storage	5,000 sacks	
BOP & Well Control Equipment		
BOP Rams	(2) Cameron double rams 18-3/4" 15k psi BOP	
BOP Annular	(1) Cameron 18-3/4" 10,000psi annular preventer	
BOP Handling	(2) J D Neuhaus EH-75 BOP main hoists, rated 75mt each	
Diverter	Vetco KFDJ 500, 49-1/2" diverter rated to 500psi with (1)16" flow line, (2) 12" overboard, (1) 6" deluge and (1) 3" fill line	
Mooring Equipment		
Mooring Winches	(4) Mentrade electric winches rated at 31mt capacity 63.5mt brake holding	
Anchor Lines	3000ft x 1-1/2" galvanized wire rope	
Anchors	(4) Flipper Delta anchor	
Cranes		
Cranes	(3) Baker Marine cranes, 50mt capacity,120ft boom	
Special Features & Other Information		
СТИ	TSC 225mt Vertical Load and 25mt Lateral Load - hydraulic driven @ 4.66 m and 10.66 m from AFT transom	
RPD System	Yes	
Helideck	Rated for Sikorsky S-61 and S-92 helicopters. CAP 437	
Offline Systems:		
Iron Roughneck	(1) Cameron JiM 10 T-P Iron Roughneck. 3-1/2" to 9-3/4" OD	
MPC	FORUM MPC (Multi-Purpose Crane) of 6,000 lbs SWL at all radii, crane boom end is adapted for mounting of a 280-kg man-basket	
OA Crane	OAC (Offline Activity Crane) Forum 10mt derrick mounted for offline pipe handling	



Emergency Power



